

Method and apparatus for high availability and caching data storage devices

Patent Number: ☐ EP0889410, A3, B1
Publication date: 1999-01-07
Inventor(s): CHONG FAY (US)
Applicant(s): SUN MICROSYSTEMS INC (US)
Requested Patent: ☐ JP11120092
Application Number: EP19980305034 19980625
Priority Number(s): US19970883923 19970626
IPC Classification: G06F11/20
EC Classification: G06F11/20L
Equivalents: DE69811150D, ☐ US6070251
Cited Documents: EP0747822; WO9707458; US5588110; JP60007548

Abstract

A method and apparatus for high availability and caching data storage devices. According to a preferred embodiment of the invention, there is provided an apparatus. The apparatus comprises a primary controller, a secondary controller having the same address as that of the primary controller, a switching circuit coupled to the primary and secondary controllers, and a control circuit coupled to the switching circuit. According to this preferred embodiment of the invention, in a normal operation, the control circuit sets the switching circuit so that the primary controller receives and responds to input data supplied from a host, and the secondary controller receives the input data. In a fail-over operation in which the primary controller fails, the control circuit sets the switching circuit so that the primary controller is disabled, and the secondary controller receives and responds to the input data supplied from the host. The fail-over is transparent to the host. The apparatus may further comprise a data storage device coupled to both the primary and secondary controllers. An alternative preferred

embodiment of the invention is also provided. 

Data supplied from the esp@cenet database - I2